The S1L series is a versatile volumetric LED troffer that offers even illumination without dark areas common with traditional troffers. It is ideal for surface ceiling applications such as offices, hospitals and schools.

S1L surface volumetric



Features and Specifications:

Construction:
- Custom designed ribbed frosted diffuser fully obscures LEDs and offers a completely clean, fully luminous appearance with no LED hot spots
- Reflectors are steel finished in a custom matte white finish with 91% reflectivity

Size Options:
- Available in 1x4, 2x2 or 2x4 sizes

Listing & Ratings:
- All electrical components are U.L. listed or recognized
- All fixtures are U.L. Certified and Union made in the USA
- Meets Buy America Act (BAA), BABA Compliant

Mounting Options:
- Surface ceiling or suspended mount

Driver:
- Universal voltage 120-277V standard
- 0-10V or Lutron dimming optional
- Custom driver tuning available for specific lumen requirements

Warranty:
- 5 years - part replacement only (see our terms & conditions page at www.lamarled.com for details)

See page 2 for lumen chart & dimensions

Ordering Guide / Example **S1L22M-40**

S1L

Series	Size	Power	CCT	General Options
S1L = Surface single lens	**14** = 1x4 **22** = 2x2 **24** = 2x4	**L** = Low **M** = Medium **H** = High	**80 CRI** **30** = 3000K **35** = 3500K **40** = 4000K **50** = 5000K **90 CRI** **930** = 3000K **935** = 3500K **940** = 4000K **950** = 5000K	**EM** = Emergency pack >90 min., >500 lumens **EMH** = Emergency pack >90 min., >1400 lumens (4ft only) **EMB** = BABA Compliant Emergency pack >90 min., >500 lumens **D** = 0-10V dimming to 1% **DTD** = 0-10V Dim to Dark **LDH** = Lutron EcoSystem Hi-lume digital 1% w/Fade to Black **AWNR** = Lutron Athena wireless node integral fixture control (RF only) **AWNS** = Lutron Athena wireless node integral fixture control (RF with daylight and occupancy sensing)

Consult factory for additional options not shown or listed

Correlated Color Temperatures (CCTs) fall within the nominal range as per ANSI C78.377A

Project Information:

Job Name: Fixture Type:

Catalog #: Date:

Comments:

Certification & Listings:


LAMARLED 1150 Motor Pkwy, Central Islip, NY 11722 | tel 631.777.7700 fax 516.333.7695 | www.lamarled.com

S1L surface volumetric


BEFORE INSTALLATION, PLEASE CONSULT YOUR LOCAL ORDINANCES AND BUILDING CODES FOR COMPLIANCE


Dimensions

2x2 and 2x4 Models





END VIEW





1x4 Model





Lumen/Wattage Chart - 4000K

S1L LED WATTAGE/LUMEN CHART

	1x4 Low	2x2 Low	2x4 Low
	4000K	4000K	4000K
LUMENS	2487	2602	4146
WATTAGE	23.7	25.2	41.3
LPW	105	103	100
	1x4 Medium	2x2 Medium	2x4 Medium
	4000K	4000K	4000K
LUMENS	3417	3400	6133
WATTAGE	33.9	34.5	56.8
LPW	101	99	108
	1x4 High	2x2 High	2x4 High
	4000K	4000K	4000K
LUMENS	4294	4273	8293
WATTAGE	45.4	45.6	82.7
LPW	95	94	100

Lumen Multipliers

3000K	.952
3500K	.968
5000K	1.03

LAMAR LED assumes no responsibility for misapplication of fixtures
Due to the rapid advancements in LED technology, please consult our website for the most current technical data.

Specifications subject to change without notice - Rev 1026